



LV-AL Series LED Area Light

100–200W & 200–300W Selectable | 5000K | Bronze

Product Highlights

- Selectable wattage: 100W / 150W / 200W and 200W / 240W / 300W
- Up to 150 lm/W high efficiency
- 5000K standard color temperature
- 0-10V dimming standard
- Durable die-cast aluminum housing
- Slip fitter and direct mount options available

Ordering Guide

Series	Wattage	CCT	Voltage	Mount	Finish
LV-AL-1	100/150/200W	5000K	120-277V	Slip / Direct	Bronze
LV-AL-2	200/240/300W	5000K	120-277V	Slip / Direct	Bronze

Specifications

Model	Wattage	Lumens	Voltage	CCT	CRI	PF
LV-AL-100/150/200	100/150/200W	Up to 30,000 lm	120-277V	5000K	≥80	≥0.9
LV-AL-200/240/300	200/240/300W	Up to 45,000 lm	120-277V	5000K	≥80	≥0.9


Electrical

Input Voltage: 120-277V | PF ≥0.9 | THD <20% | -40°F to 113°F

Construction & Materials

Die-cast aluminum housing. Bronze powder coat. IP65 rated. UV-resistant lens.

Product Images



Plainview Lighting | info@plainviewlighting.com | 331-808-3095